BOLLARD ROBOC 20528



PAGE 1/2

BOLLARD ROBOC 20528 (ON/OFF, DALI)




The PRECILUM GARDEN range brings the bollard BOLLARD ROBOC to the outdoor world of garden lighting. Bringing the flexibility to outdoor aplication, this lighting fixture is ideally suited to use in the gardens and parks. Two independent modules to be adjusted are ideal solution to iluminate different areas in your garden.



PRODUCT SPECIFICATIONS

- INPUT VOLTAGE: 230V 50 Hz
- EFFICIENCY: > 92%
- POWER CONSUMPTION: 15W ... 2 6 × 1W LED (up to 1152 lm)
- LIFETIME: > 50 000 hours
- THERMAL PROTECTION: yes
- LED DEVICE: OSRAM
- LED VARIANTS: 3000K, 4000K, 5000K and other according requirement
- WEIGHT: 4,74 kg
- OPERATING TEMPERATURE: range -20 °C to +40°C
- ENVIRONMENT: for OUTDOOR use, IP54
- HOUSING COLOR: RAL 7015 and other RAL according requirement
- MATERIALS: housing-die-cast Aluminium, cover-tempered glass
- CONTROL: ON / OFF or DALI

DIMENSIONAL DRAWINGS






PAGE 2/2

BOLLARD ROBOC 20528 (ON/OFF, DALI)

PHOTOMETRICS

Variants: 5°, 8°, 15°, 30°, 60°



ACCESSORIES

See WEB site

CONNECTION

SERIAL CONNECTION MUST BE DONE BY CERTIFIED ELECTRICIAN