

PIPE COB (ON/OFF, DALI)




Suspended luminaire with DALI integrated driver, tubus PMMA frosted and length of tubus according project requirement. Optical options 25 / 40 / 60deg available. Passive cooling of LED/COB with optimised heat sink geometry. COB (Chip on Board) technology for maximum efficiency. No multiple shadows, energy-efficient LEDs with very good colour rendering; binning initial ≤ 3 MacAdam; available in the light colours 2700K, 3000K and 4000K or other special COB for Fresh MEAT and FOOD areas; CRI ≥ 90 ; min. 80% of the luminous flux after 50000 hours; precise radiation characteristic with three different beam angles; installed and exchanged without tools; protection class IP 20, DALI dimmable.



PRODUCT SPECIFICATIONS

- INPUT VOLTAGE: 230V 50 Hz
- EFFICIENCY: > 93%
- POWER CONSUMPTION: 14W (up to 1690 lm)
- LIFETIME: > 100 000 hours
- THERMAL PROTECTION: yes
- LED DEVICE: CITIZEN, Bridgelux, OSRAM, COB
- LED VARIANTS: 2700K, 3000K, 4000K, 5000K and other according requirement
- WEIGHT: 1,3 kg
- OPERATING TEMPERATURE: range -20 °C to +40°C
- ENVIRONMENT: for INDOOR use, IP20
- HOUSING COLOR: frosted PMMA, transparent white
- MATERIALS: inner-housing Aluminium, outer tubus-PMMA frosted tube diameter=150 mm
- PRODUCTION MATERIAL OF DIFFUSER: PMMA frosted
- DRIVER TYPE: OPTOTRONIC® OTi DALI 15/220-240/550 D LT2 L
- CONTROL: ON / OFF or DALI

DIMENSIONAL DRAWINGS




INSTALLATION PICTURE



PIPE COB (ON/OFF, DALI)

PHOTOMETRICS



ACCESSORIES

- See WEB site

CONNECTION

- SERIAL CONNECTION MUST BE DONE BY CERTIFIED ELECTRICIAN