CIRCU 12 STAINLESS



PAGE 1/2

CIRCU 12 STAINLESS (ON/OFF)




Stainless steel luminaire with high IP coverage for use in fountains and ponds. Low Voltage Supply, Class III.



PRODUCT SPECIFICATIONS

- INPUT VOLTAGE: 24V DC
- EFFICIENCY: > 92%
- POWER CONSUMPTION: 12 × 1W LED ... 14W (up to 1415 lm)
- LIFETIME: > 70 000 hours
- THERMAL PROTECTION: yes
- LED DEVICE: OSRAM
- LED VARIANTS: 3000K ,4000K ,5000K and other according requirement
- WEIGHT: 1,39 kg
- OPERATING TEMPERATURE: range -20 °C to +40°C
- ENVIRONMENT: four OUTDOOR use, IP68 ... 3 m
- HOUSING COLOR: stainless steel
- MATERIALS: housing-stainless steel, cover-tempered glass
- CONTROL: ON / OFF

DIMENSIONAL DRAWINGS




CIRCU 12 STAINLESS



PAGE 2/2

CIRCU 12 STAINLESS (ON/OFF)

PHOTOMETRICS



ACCESSORIES

See WEB site

CONNECTION

SERIAL CONNECTION MUST BE DONE BY CERTIFIED ELECTRICIAN